

# DUCKY

Clear Water Repellent For Walls



## Owl Distribution UK & Ireland

144 Slaney Close, Dublin Industrial Estate,  
Glasnevin, Dublin. D11 X343  
UK 0845 528 1480  
Irl 01 830 22 50  
[www.owlwaterproofing.co.uk](http://www.owlwaterproofing.co.uk)



# OWL



## Ducky solves problem of wind driven rain soaking through masonry

### BEFORE THE APPLICATION OF DUCKY



A wet wall is a cold wall



**READY TO APPLY**  
**COMPLETELY INVISIBLE**  
**100% WATER REPELLENT**

## DUCKY: water repellent treatment for brick, concrete and stone walls

### AFTER THE APPLICATION OF DUCKY



A dry wall is a warm wall



## WATER INFILTRATION CAN CAUSE MANY PROBLEMS...



### PHYSICAL AND AESTHETIC DAMAGES:

- Increased costs for winter heating
- Increase in interstitial condensation due to cold walls
- Formation of mould inside the house that creates an unhealthy environment



### ECONOMIC AND HEALTH ISSUES:

- A wet wall is a poorly insulated wall - more heat lost.
- Colder building means more costly heating required
- Cold wet walls increases likelihood of condensation & toxic mould

## KEY BENEFITS

### ☒ DEEP PENETRATION

Protects brick, stone and concrete from wind driven rain penetration, while allowing the masonry to breathe and retain its original look.

### ☒ IMPROVING THE THERMAL PERFORMANCE OF THE MASONRY

Porous masonry materials such as brick, stone, concrete, and mortar are worse insulators when they are wet.

### ☒ REDUCE HEAT LOSS

By preventing the absorption of water, Ducky ensures that the insulation properties of the masonry are maximised throughout the year.

### ☒ EASY TO APPLY

The product is ready to use and it is the perfect solution for a do-it-yourself and durable intervention.

### ☒ SOLVENT FREE

Not dangerous for health and environment

## APPLICATION



Ducky is based on **silanes and siloxanes** which form a **water-repellent matrix** within the masonry. With a low molecular weight **Ducky penetrate deeply** into the substrate.

Ducky is a **transparent, breathable, water-repellent** treatment for **brick, concrete and stone walls**. It is applied to the wall surface using a **roller or brush**. Once Ducky has been applied to the wall surface and cured, it form a **water-repellent barrier**.

**Please note:** Larger cracks and mortar lines will still need to be filled or repointed with a sand/cement or sand/lime mix before applying Ducky. The product should only be applied to dry, porous surfaces. Do not apply on to sealed or painted surfaces.